




METAL EXPANSION JOINTS





TYPES OF EXPANSION JOINTS


CIRCULAR EXPANSION JOINTS


Single or multiple ply Diametre ranging from 15 to 8000 mm



















Gimbal


RECTANGULAR EXPANSION JOINTS

Limitless dimensions



Rounded Corners





SINGLE CONVOLUTION



SELECTION CRITERIA

- Temperature resistance
- Resistance to corrosion
- Forming capacity
- Mechanical characteristics

Flexibility

MAIN ADVANTAGES

- High pressure resistant
- Flexibility
- Low spring rates
- Low maintenance



MATERIALS

Materials used in manufacturing are:

- Austenitic Steels as AISI 321, 304, 316, 316L. 316Ti, 309, 253 Ma, 254 SMO, etc.
- Nickel Alloys such as Monel 400, Inconel 600, 625, Incoloy 800 H, Hastelloy, etc.

STANDARDS

Metal Expansion Joints are designed, manufactured and tested according to Internationally Recognized Codes and Standards :

- E.J.M.A. (Expansion Joints Manufacturers Association, Inc.),
- · ASME,
- AD Merkblatter, etc.

QUALITY CONTROL

A WIDE RANGE OF TESTS CAN BE CARRIED OUT ON CUSTOMERS REQUEST

- Radiography
- Liquid penetration
- Ultrasonic
- Magnetic particles
- · Hydraulic pressure
- Materials analysis
- Spring rates
- Helium leak detection

SERVICES

- Technical assistance for the design of piping systems
- On site inspection
- Measurements





